



**In Union,
there is strength.**



UNITHANE 8120 NF

Revision Date: 07/21

Reviewed:07/21/21

RECOMMENDED FOR USE WITH:

Leather

UNITHANE 8120 NF is a soft, waterborne, NMP-free topcoat that can be used on almost any type of leather. Normal application is by either spray or by roll coater and a starting formulation would be 1:1 with water. UNITHANE 8120 NF gives a pleasant feel and has good adhesion and flexibility. UNITHANE 8120 NF can be cross-linked with external crosslinkers to improve physical properties if needed.

A starting formula for spray application is as follows (All parts by weight):

UNITHANE 8120 NF 50

WATER 50

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Bright, Aircraft, Upholstery, Shoe, Handbag, Synthetic Leather

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 19 - 21

pH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 150 - 500 cps.

VOC (% OF TOTAL WEIGHT): 7.5-8.5

SPECIFIC GRAVITY: 1.01-1.04

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 12 months

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
